



SpECseal Firesafe Acrylic

FIRE RESISTANT ACRYLIC SEALANT

DESCRIPTION

SpECseal Firesafe Acrylic is a specially formulated water based, acrylic sealer for both indoor and outdoor use. It is a non-flammable product that provides permanent flexibility and has excellent water resistance and sealing characteristics.

TYPICAL USES

- Sealer for indoor and outdoor use
- Low to high pressure metal air distribution systems

ADVANTAGES

- Non-Flammable
- Permanently flexible
- Excellent water resistance
- Non-Staining
- Paintable
- Mold and mildew resistance

TECHNICAL DATA

Colours	White and Grey
Surface Burning	
Characteristics	Class "A"
Flame Spread (FSI)	0
Smoke Developed (SD)	15
Viscosity Flow	Non-sag
Skin formation	5 - 7 minutes
Tack-Free Time	20 minutes
Specific Gravity	1.60 - 1.65

APPLICATION

Joint Preparation

Surface should be clean, dry and free from oil grease or any other contamination. Thoroughly rinse surface & allow to dry completely before caulking & painting.

Clip off tip of spout @ a 45° angle to desired size. Load cartridge into caulking gun & apply using steady, even pressure to completely bridge joints. Smooth caulk using a Caulk Smoother or a damp cloth for a neat appearance. Wipe away excess with a damp cloth before surface skins over. Protect from exposure to rain or water for 72 hrs for adequate curing.

FOR BEST RESULTS

- Do not use for joints subject to heavy abrasion or wear
- Prime bare surfaces before caulking
- For a neat, straight bead edge, mask both sides of joint with masking tape. Remove promptly before skin forms
- Do not "overtighten" the applied caulk, leaving too little caulk to perform, following cure

LIMITATIONS

- Apply only to clean, dry, frost-free surfaces
- Do not apply when rain or freezing temperatures are expected
- Protect from rain & exposure to water for 72 hrs
- Not recommended for use in marine applications, below grade applications or under water applications
- Not recommended for use on automobiles or aquariums

EQUIPMENT CLEANING

Clean equipment with water and mild soap.

APPLICATION TEMPERATURE RANGE

Minimum	5°C
Maximum	50°C

PACKAGING & YIELD

SpECseal Firesafe Acrylic is supplied in cartridges of 280ml.

STORAGE & SHELF LIFE

To maintain the shelf life of 12 months, **SpECseal Firesafe Acrylic** should be stored in the original sealed-tight container at temperatures between 5 °C and 30 °C.

HEALTH & SAFETY

Contact with skin and eyes should be avoided. It is essential that adequate ventilation is provided and all personnel should avoid inhaling the vapours produced. If working is necessary in confined areas it is strongly recommended that sealed respiratory equipment is utilized.

Eye Contact

Rinse with copious amounts of clean water and seek medical attention.

Skin Contact

Rinse with copious amounts of clean water followed by thorough cleaning with soap and water. **DO NOT USE SOLVENTS**

Ingestion

Seek immediate medical attention. **DO NOT INDUCE VOMITING**

Issue 1C: 12/2020

QA-054

Whilst the information and/or specifications given are, to the best of our knowledge, true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents or distributors as the conditions of use and labour involved are beyond our control.

If it is proven that the product does not perform as described in our TDS, SpEC's liability extends solely to the free replacement of product, once the claim has been accepted after due investigation by SpEC. SpEC will not entertain any claims involving any form of consequential costs or damages such as shipping costs, custom duties, damages to third parties, damages to structures, penalties from delay of a project or any other form of consequential damage.

SPECIALITY ENGINEERING CHEMICALS

PO Box 61347, Dubai, United Arab Emirates. Telephone: +971 4 883 6662, Fax: +971 4 883 7696

E-mail: info@spec.ae

www.spec.ae