







# MATERIAL SAFETY DATA SHEET

# 1. Identification of the Substance / Preparation and of the Company Undertaking

Product Name: SpECtop HF Filler

Product Use: Floorings

Company: Speciality Engineering Chemicals FZE

Address: P. O. Box 61347, Dubai, U.A.E.

Telephone: +971-4-8836662 Facsimile: +971-4-8837696

E-mail: info@spec.ae Web site: www.spec.ae

# 2. Composition / Information on Ingredients

Composition: Graded silica sands.

Hazardous Ingredient(s) Symbol CAS No. Risk Phrases %

Cement Xi 65997-15-1 R36/37/38 20 - 30

Calcium Hydroxide Xn 1305-62-0 R20/48 1 - 10

#### 3. Hazards Identification

Irritating to eyes. respiratory system and skin. Risk of serious damage to eyes



#### 4. First Aid Measures

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth

to an unconscious person.

Eyes: Check for and remove contact lenses if any. irrigate copious amount of water for several minutes

keeping eye lids open. Obtain medical attention if problem persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser immediately. Obtain medical attention if

problem persists.

Inhalation: Remove to fresh air. If not breathing or irregular breathing, provide artificial respiration. Seek medical

attention if the problem continues.

Ingestion: Rinse out mouth, drink water. Do not induce vomiting. Obtain medical attention if symptoms persist.

# 5. Fire Fighting Measures

Suitable Extinguishing Media: Not flammable.

Special Exposure Hazards: None.

Special Protective Equipment: None.

#### 6. Accidental Release Measures

Personal Precautions: Wear gloves and other suitable protective clothing.

Issue: 01 QA-041 Date: 22-Jan-20 Product Name: SpECtop HF filler Page: 1 of 3

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Gather into containers. Avoid formation of dust in atmosphere. Residue may be

flushed to the drains with large volume of water.

## 7. Handling and Storage

Handling: Avoid creating dust. Use eye/face protection. Ensure adequate ventilation.

Storage: Store in dry and cool area.

Decontamination Procedure: Gather into containers. Avoid formation of dust in atmosphere.

# 8. Exposure Controls / Personal Protection

Occupational Exposure Limits: None assigned

Substance 8 Hour TWA STEL Source/Other Information

Cement: 10 mgm<sup>-3</sup> —— EH 40

Calcium hydroxide: 5 mgm<sup>-3</sup> —— EH 40

Engineering Control Measures: atmospheric levels of dust must be maintained within the Occupational exposure

standard. Where mechanical methods are in adequate, appropriate personal protec-

tion equipment must be used.

Personal Protective Equipment: Impervious gloves, goggles, approved dust mask.

#### 9. Physical and Chemical Properties

State: Powder

Colour: Colourless

Odour: Odourless

# 10. Stability and Reactivity

Stability: Stable under recommended conditions.

Conditions to avoid: Exposure to air. Contamination with water.

Materials to avoid: None.

Hazardous Decomposition products: None.

## 11. Toxicological Information

May cause transient irritation to eyes

May cause irritation by inhalation and if swallowed.

# 12. Ecological Information

When used and disposed as intended, no adverse environmental effects are foreseen. Expected to be not readily bio-degradable. Bio-accumulative potential and ecotoxicity are not determined.

Issue: 01	QA-041	Date: 22-Jan-20	Product Name: SpECtop HF filler	Page: 2 of 3

# 13. Disposal Considerations

Disposal must be in accordance with local and national legislation.

Do not allow to enter drains or watercourses. Material and container must be disposed as hazardous waste.

# 14. Transport Information

Proper Shipping name: Graded silica sands

IMDG Class: Not classified as hazardous for transport.

IATA Class: Not classified as hazardous for transport.

ADR/RID: Not classified as hazardous for transport.

#### 15. Regulatory Information

**EU Regulations:** The product is labeled as follows, in accordance with local regulations.

Hazard Symbol(s): Xi

Contains: Silica, Cement

Risk Phrases: R20 - Harmful by inhalation

R41 - Risk of serious damage to the eyes

R48 - Danger of serious damage to health by prolonged exposure through inhalation

Safety Phrases: S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice

S39 - Wear eye/face protection

# 16. Other Information

Issue no.: 1

Issue date: 22-Jan-20

Issued by: SpEC Technical Department

No liability accepted for any injury, loss, damage or cost arising directly or indirectly from the use of any information contained within this MSDS since the customers treatment of the product is necessarily out of our control.

The data given above is based upon current knowledge and experience. This safety sheet is intended to describe our products in terms of their safety requirements. It does not guarantee the properties of the products described.

Issue: 01 | QA-041 | Date: 22-Jan-20 | Product Name: SpECtop HF filler | Page: 3 of 3