







# MATERIAL SAFETY DATA SHEET

### 1. Identification of the Substance / Preparation and of the Company Undertaking

Product Name: SpECseal 200 Primer Hardener

Product Use: Sealant

Company: Speciality Engineering Chemicals FZE

Address: P. O. Box 61347, Dubai, U.A.E.

Telephone: +971-4-8836662 Facsimile: +971-4-8837696

E-mail: info@spec.ae Web site: www.spec.ae

## 2. Composition / Information on Ingredients

Composition: Epoxy hardener and solvents.

Hazardous Ingredient(s) Symbol CAS No. Risk Phrases %

Aliphatic Polyamines Xn 2855-13-2 R34/R36/R43 100

#### 3. Hazards Identification

Non-hazardous Harmful if inhaled



## 4. First Aid Measures

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth

to an unconscious person.

Eyes: Check for and remove contact lenses if any. Irrigate copious amount of water for several minutes

keeping eye lids open. Obtain medical attention if problem persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser immediately. Obtain medical attention if

problem persists.

Inhalation: Remove to fresh air. If not breathing or irregular breathing, provide artificial respiration. Seek medical

attention if the problem continues.

Ingestion: Do not induce vomiting. Obtain medical attention and show the container or label.

## 5. Fire Fighting Measures

Suitable Extinguishing Media: CO<sub>2</sub> / Dry chemical powder. Do not use water jets.

Special Exposure Hazards: Toxic fumes.

Special Protective Equipment: Self - contained breathing apparatus.

## 6. Accidental Release Measures

Personal Precautions: Wear gloves and other suitable protective clothing.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Issue: 03 | QA-041 | Date: 05-Jan-25 | Product Name: SpECseal 200 Primer hardener | Page: 1 of 4

Decontamination Procedures: Soak-up with inert absorbent or contain and remove by best available means. Gather

into containers. Dispose of as hazardous waste.

### 7. Handling and Storage

Handling: Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product.

Ensure adequate ventilation.

Storage: Keep containers dry, cool and tightly closed.

Decontamination Procedure: Soak-up with inert absorbent or contain and remove by best available means. Gather

into containers. Dispose of as waste.

#### 8. Exposure Controls / Personal Protection

Occupational Exposure Limits: None assigned

Substance 8 Hour TWA STEL Source/Other Information

Xylene, mixed isomers 435 mgm<sup>-3</sup> 650 mgm<sup>-3</sup> EH 40

Engineering Control Measures: Use with adequate general and local exhaust ventilation

Personal Protective Equipment: Impervious gloves, safety goggles, plastic apron.

## 9. Physical and Chemical Properties

State: Liquid

Colour: Amber

Odour: Earthy

Flash Point (°C): >60

Specific gravity: 0.90

Viscosity: 0.5

Solubility: Insoluble

#### 10. Stability and Reactivity

Stability: Stable under recommended conditions.

Conditions to avoid: Not known.

Materials to avoid: Strong acids, alkalies and oxidising agents.

Hazardous Decomposition products: Carbon monoxide. Irritant fumes.

#### 11. Toxicological Information

There are no date available on the preparation itself. This has been assessed following the conventional method of the Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this product may be a skin sensitiser and irritant. Harmful by inhalation. Vapours may cause headaches, dizziness and central nervous systems depression.

LD50 oral, rat: 1030mg/kg

Issue: 03	0A-041	Date: 05-Jan-25	Product Name: SpECseal 200 Primer hardener	Page: 2 of 4
1155UC. US	IQA-OTI	1Date, 05-jaii-25	i roduct Name. Speosear 200 i miner nardener	II ago. Z oi T

#### 12. Ecological Information

Environmental Assessment: Contains volatile organic compounds.

When used and disposed as intended, no adverse environmental effects are foreseen. Expected to be not readily biodegradable. Bio-accumulative potential and ecotoxicity are not determined.

## 13. Disposal Considerations

Disposal must be in accordance with local and national legislation.

Do not allow to enter drains or watercourses. Material and container must be disposed as hazardous waste.

# 14. Transport Information

Proper shipping name: Not classified as hazardous for transport

UN Number: Not classified as hazardous for transport

IMO Class: Not classified as hazardous for transport

IATA/ICAO Class: Not classified as hazardous for transport

ADR Class: Not classified as hazardous for transport

Subsidiary risk: -

Packing Group: -

Label(s):

Additional Information

ADR-HIN: -

IMDG-EMS: - Marine Pollutant: No

IMO:

#### 15. Regulatory Information

**EU Regulations:** The product is labeled as follows, in accordance with local regulations.

Hazard Symbol(s): Xn

Contains: Polyamine adduct

Risk Phrases: R20 - Harmful by inhalation

R36 - Irritating to eyes R38 - Irritating to skin

Safety Phrases: S28 - After contact with skin, wash immediately with plenty of water

S36 - Wear suitable protective clothing

S38 - In case of insufficient ventilation, wear suitable respiratory equipment

EC Directives: Dangerous Substance Directive, 67/548/EEC and adaptations.

Dangerous Preparations Directive, 88/379/EEC. Safety Data Sheets Directive, 91/155/EEC.

Statutory Instruments: Chemicals (Hazard Information and Packaging) Regs. 1993 (SI 1746).

Control of Substances Hazardous to Health Regs. 1988 (SI 1657).

Issue: 03 QA-041 Date: 05-Jan-25 Product Name: SpECseal 200 Primer hardener Page: 3 of 4

Health and Safety at Work, etc. Act 1974.

**Environmental Protection Act 1990.** 

Highly Flammable Liquids & Liquefied Petroleum Gases Regs. 1972 (SI 917)

Codes of Practice: Waste Management. The Duty of Care.

Operational Provisions of the Road Traffic (Carriage of Dangerous Substances in packages,

etc.) Regs 1986 (COP17)

Guidance Notes: Occupational skin diseases: health and safety precautions (EH26).

Storage of packaged dangerous substances[HS(G)71].

The storage of highly flammable liquids (CS 2).

The above publications are available from HMSO.

#### 16. Other Information

Issue no.: 3

Issue date: 05-Jan-25

Issued by: SpEC Technical Department

No liability accepted for any injury, loss, damage or cost arising directly or indirectly from the use of any information contained within this MSDS since the customers treatment of the product is necessarily out of our control.

The data given above is based upon current knowledge and experience. This safety sheet is intended to describe our products in terms of their safety requirements. It does not guarantee the properties of the products described.