



SpECTite Acrybond

ACRYLIC VINYL ADHESIVE

DESCRIPTION

SpECTite Acrybond is a synthetic acrylic emulsion based flooring adhesive for sticking PVC Sheets, PVC Tiles, Carpets, etc., to most concrete and wooden surfaces.

TYPICAL USES

- Adhesive for PVC Sheets, and PVC Tiles.
- Adhesive for Wood, plywood, MDF, etc.
- Adhesive for many types of carpets.

ADVANTAGES

- Easy to apply with standard tools and equipment
- Complying with LEED requirements
- One component and ready to use – no mixing required
- Application on one side of the adherents
- Excellent resistance to water and heat
- Water based – environmental friendly
- Excellent bonding and peel strength

TECHNICAL DATA

Appearance	Off-White Paste
Solids Content	~75%
Setting Time	24 hours
Application Temperature	+5 °C - +40 °C

APPLICATION

SpECTite Acrybond is a single component adhesive requires no pre-blending. Apply a uniform coat of **SpECTite Acrybond** to the well prepared flooring using a “V” notched trowel. The spreading rate can be about 5 square metre per kg of adhesive. The adhesive shall be allowed to become “tacky” before laying the vinyl sheets / tiles / carpets. Care should

be taken not to allow the adhesive to cure. The vinyl sheets / tiles shall be laid on the adhesive. Use a roller in both the directions to ensure there is a good transfer of adhesive to the back of the vinyl or carpet flooring.

EQUIPMENT CLEANING

SpECTite Acrybond may be removed with water immediately after use.

Cured material can only be removed mechanically.

PACKAGING AND YIELD

SpECTite Acrybond is supplied in 5 kg and 24 kg units. Application rate is 5 m²/kg.

STORAGE AND SHELF LIFE

SpECTite Acrybond has a shelf life of 12 months when stored in original, unopened containers in a cool, dry environment.

HEALTH AND SAFETY

Contact with skin and eyes should be avoided.

Issue 2: 11/2022

QA-054

Whilst the information and/or specifications given are, to the best of our knowledge, true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents or distributors as the conditions of use and labour involved are beyond our control.

If it is proven that the product does not perform as described in our TDS, SpEC's liability extends solely to the free replacement of product, once the claim has been accepted after due investigation by SpEC. SpEC will not entertain any claims involving any form of consequential costs or damages such as shipping costs, custom duties, damages to third parties, damages to structures, penalties from delay of a project or any other form of consequential damage.

SPECIALITY ENGINEERING CHEMICALS

PO Box 61347, Dubai, United Arab Emirates. Telephone: +971 4 883 6662, Fax: +971 4 883 7696

E-mail: info@spec.ae

www.spec.ae